

Tipo Typ Type Type	Portata kg (lb) Tragkraft kg (lb) Coil weight kg (lb) Charge kg (lb)	Larghezza Nastro mm (in) Bandbreite mm (in) Strip width mm (in) Largeur bande mm (in)	Espansione mandrino mm (in) Spindelspreizung mm (in) Mandrel expansion mm (in) Expansion du mandrin mm (in)	Dia. esterno mm (in) Aussendurchm. mm (in) Outer dia. mm (in) Dia. externe mm (in)
SLF/SLM 500	500 (1100)	300 (11,811)	370-630 (14,567-24,803)	Ø 1500 (59,055)
SLF/SLM 1000	1000 (2200)	300 (11,811)	370-630 (14,567-24,803)	Ø 1500 (59,055)
SLF/SLM 1500.1	1500 (3300)	400 (15,748)	370-630 (14,567-24,803)	Ø 1500 (59,055)
SLF/SLM 1500.2	1500 (3300)	500 (19,685)	370-630 (14,567-24,803)	Ø 1500 (59,055)
SLF/SLM 2000.1	2000 (4400)	400 (15,748)	370-630 (14,567-24,803)	Ø 1500 (59,055)
SLF/SLM 2000.2	2000 (4400)	500 (19,685)	370-630 (14,567-24,803)	Ø 1500 (59,055)
SLF/SLM 2000.3	2000 (4400)	600 (23,622)	370-630 (14,567-24,803)	Ø 1500 (59,055)

- SLF: aspi non motorizzati - SLM: aspi motorizzati
- SLF: nicht angetriebene Haspeln - SLM: angetriebene Haspeln
- SLF: non powered decoilers - SLM: powered decoilers
- SLF: dévidoirs non motorisés - SLM: dévidoirs motorisés